

## N-TRON 900B Modular Industrial Ethernet Switch

*Built to Operate Reliably in Industrial Applications*

The N-TRON™ 900B Modular Industrial Ethernet Switch offers outstanding performance, ease of use, and flexible expansion options. It is ideally suited for connecting Ethernet enabled industrial equipment such as PLC's, Industrial PC's, Ethernet I/O and Data Acquisition Equipment.

### Product Features

- Full IEEE 802.3 Compliance
- Up to Twenty Four 10/100BaseTX Ports
- Up to Twelve 100BaseFX Ports, ST or SC
- Extended Environmental Specifications
- Scaleable Three Slot Switch
- Flexible Combinations of TX & FX Modules
- Support for Full/Half Duplex Operation
- LED Link/Activity Status Indication
- Auto Sensing Speed and Flow Control
- Store-and-Forward Technology
- Auto Cable Sensing (MDIX)
- Up to 2.6 Gb/s Maximum Throughput
- Rugged Industrial DIN-Rail Enclosure
- Redundant Power Inputs (10-30 VDC)
- N-View Switch Monitoring Option

### Flexibility

Mix and match fiber ports with twisted pair ports. Three module slots are available for the installation of 900 Series expansion modules providing maximum flexibility. Up to 24 twisted pair 10/100BaseTX or 12 100BaseFX fiber ports can be installed with multiple combinations available in between. Any expansion module can be installed in any slot.

### Industrial Packaging and Specifications

The 900B is designed to operate in industrial environments. It is housed in a rugged steel enclosure and standard 35mm DIN-RAIL mounting. An Optional kit is available for rackmount applications. Like all N-TRON products, the 900B comes standard with extended temperature ratings, extended shock and vibration specs, redundant power inputs, and a high MTBF.



### Ease of Use

The 900B is a plug and play device. No configuration is required. All 10/100BaseTX ports are auto sensing and auto configuring. Each port is automatically set for maximum speed and performance. In addition, each twisted pair port has an Auto MDIX feature, eliminating the need for crossover cables.

LED's are provided to display the link status and activity of each port as well as power on/off status.

### Performance

The 900B uses "state of the art" Ethernet switching technology. This eliminates network collisions and increases network determinism. Up to 12,000 MAC addresses (4,000 per module) are supported enabling sophisticated and complex network architectures. A backplane speed of 2.6 Gb/s allows full wire speed capability on all ports simultaneously.

### N-View OPC Switch Monitoring Option

The N-TRON N-View OLE for Process Control (OPC) Server Software can be combined with popular HMI software packages to add network traffic monitoring, trending and alarming to any application using N-TRON switches configured with the N-View option. N-TRON's N-View OPC Server collects 41 different traffic variables per port and 5 system level variables per switch. This information can provide a complete overview of the network load, service quality, and packet traffic. OPC client software can use N-View OPC Server data to resolve network problems quickly and improve system reliability.

## Optional Expansion Modules

908TX	Slide in module with eight 10/100BaseTX Ports
902FX	Slide in module with two 100BaseFX Multimode Fiber Ports (SC or ST Connectors - 2 km fiber length)
902FXE	Slide in module with two 100BaseFX Singlemode Fiber Ports (SC or ST Connectors - 15, 40, or 80 km fiber length)
904FX	Slide in module with four 100BaseFX Multimode Fiber Ports (SC or ST Connectors - 2 km fiber length)
904FXE	Slide in module with four 100BaseFX Singlemode Fiber Ports (SC or ST Connectors - 15, 40, or 80 km fiber length)

## Specifications

### Physical

Height:	3.2"	(8.13 cm)
Width:	7.1"	(18.03 cm)
Depth:	4.1"	(10.41 cm)
Weight:	~3.0 lbs	(2.3 kg)

(note: can be mounted horizontally or vertically)

### Electrical

Input Voltage:	10-30 VDC (Redundant Inputs)
Input/Inrush Current:	200/400mA@24V per backplane
Input/Inrush Current:	250/500mA@24V per 908TX module
Input/Inrush Current:	400/800mA@24V per 902/904FX module

### Environmental

Operating Temperature:	-20°C to 70°C
Storage Temperature:	-40°C to 85°C
Operating Humidity:	10% to 95% (Non Condensing)
Operating Altitude:	0 to 10,000 ft.

### Shock and Vibration (bulkhead mounted)

Shock:	200g @ 10ms
Vibration:	1g, 10-500Hz, 3 axis
Seismic:	20g, 5-200Hz, 15s

### Reliability

MTBF:	>2M Hours (measured)
-------	----------------------

### Network Media

10BaseT:	>Cat3 Cable
100BaseTX:	>Cat5 Cable
100BaseFX	
Multimode:	50-62.5/125µm
Singlemode:	7-10/125µm

### Fiber Transceiver Characteristics

Fiber Length	2km*	15km**	40km**	80km**
TX Power Min	-19dBm	-15dBm	-5dBm	-5dBm
RX Sensitivity Max	-32dBm	-29dBm	-34dBm	-34dBm
Wavelength	1310nm	1310nm	1310nm	1550nm

\* Multimode Fiber Optic Cable  
\*\* Singlemode Fiber Optic Cable

### Recommended Wiring Clearance:

Front TX / (FX):	2" (5.08 cm) / 4" (10.16 cm)
Side:	1" (2.54 cm)

### Emissions and Safety Approvals:

FCC Part 15 Class A, CE: EN55024, EN55081, EN61000-4-2,3,4,5,6, UL Listed 1604 (US & Canada) CLASS I, DIV 2, GROUPS IIC, T4A, GOST-R Certified, RoHS Compliant

## Ordering Information

900B	Industrial Ethernet switch chassis with 3 slots for optional expansion modules with N-View Firmware Option
900B-N	Filler Panel
900B-FP	Panel Mount Kit
900-PM	19" Rackmount Kit
900-RM	Eight ports 10/100BaseTX (RJ-45)
908TX	Two ports 100BaseFX multimode fiber
902FX-XX	Two ports 100BaseFX singlemode fiber
902FXE-XX-YY	Four ports 100BaseFX multimode fiber
904FX-XX	Four ports 100BaseFX singlemode fiber
904FXE-XX-YY	

Where "XX" is: ST for ST style fiber connector  
SC for SC style fiber connector

Where "YY" is: 15 for 15km max. fiber segment length  
40 for 40km max. fiber segment length  
80 for 80km max. fiber segment length

## Contact Information France

N-Tron c/o QL3D  
Z.A. - Espace la Bonde  
6, rue des Artisans  
78760 Jouars-Pontchartrain

Tél. : 01 34 91 90 20  
Fax : 01 34 91 90 21  
email : [info@n-tron.fr](mailto:info@n-tron.fr)  
web : <http://www.n-tron.fr>

REV 080618